

WALL HEATERS



BENEFITS OF ELECTRIC WALL HEATERS

FAST HEAT

Our open coil element heaters provide rooms with instantaneous heat.

The finned tube heaters include a fan delay to ensure hot air is provided when the element is heated.

SPACE SAVER












Small, hidden designs, provide more living or working space. Wall heaters do not take up floor space and ideal for apartments, offices, basements, family rooms and entrance ways.

SUPPLEMENTAL HEATING FOR EFFICIENCY

Using alongside your HVAC system electric heaters provide supplemental heat, making your heating system more efficient and saving you money.

EASY TO INSTALL

Wall heaters do not require ducting or plumbing. They fit between studs and are recessed inside the wall to provide a clean look to any room.

MODEL	PRICE RANGE	VOLTS	WATTS RANGE	AMPS RANGE	BTU/HR RANGE	WIRE SIZE	PHASE	CFM	THERMOSTAT RANGE	FAN DELAY	POWER DISCONNECT	BMS COMPATIBLE	GRILLE COLOR	WT (LBS)
 SSARW	\$\$\$\$	120,208,240,277	540-4,800	4.5-23.1	1,843-16,378	10-12 AWG	1	100	41°F - 99°F	YES	NO	YES	○ Northern White ○ Navajo White ● Aluminum Bronze	26
 SSHO	\$\$\$	208,240,277	1,800-4,000	6.5-19.2	6,142-13,649	10-12 AWG	1	100	42°F - 99°F	YES	YES	YES	○ Northern White ● Statuary Bronze	25
 HT	\$\$	120,240	200-2,000	1.7-16.7	662-6,825	12-14 AWG	1	100	40°F - 99°F	YES	NO	NO	○ Northern White ● Gray	23
 MCSSAR	\$\$\$\$	120,208,240,277	900-4,800	7.5-23.1	3,070-16,378	10-12 AWG	1	100	40°F - 90°F	YES	YES	YES	○ Northern White ○ Navajo White ● Aluminum Bronze	28
 AWH	\$\$\$	120,208,240,277	1,500-4,800	12.5-23.1	5,118-16,378	10-14 AWG	1,3	100	40°F - 90°F	YES	NO	YES	● Statuary Bronze ○ Northern White	25
 CWH 3000	\$\$	120,208,240,277	1,500-4,800	12.5-23.1	5,118-16,378	10-14 AWG	1,3	100	40°F - 90°F	YES	YES	NO	○ Northern White	25
 LFK	\$	120,208,240,277	1,500-4,800	12.5-23.1	1,706-6,824	10-14 AWG	1	100	40°F - 90°F	YES	NO	NO	○ Northern White	23
 CWH 1000 ARCHITECTURAL	\$\$\$	120,208,240,277	500-2,000	4.2-16.7	1,706-6,824	12-14 AWG	1	65	40°F - 85°F	YES	YES	NO	● Statuary Bronze	10-11
 CWH 1000 COMMERCIAL	\$\$	120,208,240,277	500-2,000	4.2-16.7	1,706-6,824	12-14 AWG	1	65	40°F - 85°F	YES	YES	NO	○ Northern White	10-11
 COS-E	\$	120,208,240	500-2,000 CLIP-N-FIT®	4.2-16.7	1,706-6,824	10-12 AWG	1	50	40°F - 85°F	NO	NO	NO	○ Northern White	10-11
 GFR	\$\$	120, 240	375-2,400 CLIP-N-FIT®	3.1-10	1,279-8,189	10-12 AWG	1	45	40°F - 85°F	NO	NO	NO	○ Northern White	10-11